

AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

1. **(Previously Presented)** A scanning device comprising:
 a cold cathode fluorescent lamp (CCFL) for generating light;
 a heating light source for generating light;
 a timer for counting out a predetermined time period;
 a photosensor for detecting light generated by the CCFL and the heating light source; and
 a controller for controlling operations of the scanning device;
 wherein the heating light source is capable of generating more heat than the CCFL, a warm-up time period of the CCFL is longer than a warm-up time period of the heating light source, and when the timer determines that a time period starting from the CCFL being enabled reaches the predetermined time period, the controller turns off the heating light source and performs scanning of a document using the CCFL.
2. **(Original)** The scanning device of claim 1 wherein the predetermined time period is 15 to 30 seconds.
3. **(Original)** The scanning device of claim 1 wherein the scanning device is a flat bed scanner, a paper fed scanner, a copier, a Fax machine, or a multi-function product (MFP).
4. **(Original)** The scanning device of claim 1 wherein the heating light source is a metal halide lamp.
5. **(Original)** The scanning device of claim 1 wherein the CCFL and the heating light source are installed within a scanning module of the scanning device.

6. **(Original)** The scanning device of claim 1 wherein when the heating light source is enabled, the controller performs scanning of the document using the heating light source.

7. **(Currently Amended)** A multi-function product comprising:
a scanning device comprising:
a cold cathode fluorescent lamp (CCFL) for generating light;
a heating light source for generating light;
a photosensor for detecting light generated by both the CCFL and the heating light source;
a timer for counting out a predetermined time period; and
a controller for controlling operations of the scanning device; and
a start button connected to the controller, wherein when the start button is triggered, the controller does not enable the CCFL so that only the heating light source is used to scan the document;
wherein the heating light source is capable of generating more heat than the CCFL, a warm-up time period of the CCFL is longer than a warm-up time period of the heating light source, and when the timer determines that a time period starting from the CCFL being enabled reaches the predetermined time period, the controller turns off the heating light source and performs scanning of a document using the CCFL.

8. **(Previously Presented)** The multi-function product of claim 7 further comprising a control button connected to the controller, and when the control button is pressed, the controller turns on the CCFL and the heating light source simultaneously, and utilizes the CCFL and the heating light source to scan the document to shorten a scanning time period.

9. **(Canceled)**

10. **(Original)** The multi-function product of claim 7 wherein the heating light source is a metal halide lamp.

11. **(Original)** The multi-function product of claim 7 wherein the photosensor is a charge coupled device (CCD).

12. **(Previously Presented)** A device comprising:
a lamp for generating light;
a heating light source for generating light;
a timer for counting out a predetermined time period; and
a controller for controlling operations of the device;
wherein the heating light source is capable of generating more heat than the lamp, a warm-up time period of the lamp is longer than a warm-up time period of the heating light source, and when the timer determines that a time period starting from the lamp being enabled reaches the predetermined time period, the controller turns off the heating light source.

13. **(Previously Presented)** The device of claim 12, wherein the lamp is a fluorescent lamp.

14. **(Previously Presented)** The device of claim 13, wherein the lamp is a cold cathode fluorescent lamp (CCFL).

15. **(Previously Presented)** The device of claim 12, further comprising a photosensor for detecting light generated by the lamp and the heating light source.

16. **(Previously Presented)** The device of claim 1, wherein the device is a flat bed scanner, a paper fed scanner, a copier, a Fax machine, or a multi-function product (MFP).

17. **(Previously Presented)** A method for illuminating comprising:
powering a lamp and a heating light source, a warm-up time period of the lamp being longer than a warm-up time period of the heating light source;
starting a timer upon powering of the lamp and the heating light source; and
upon expiration of a set time period, ceasing to power the heating light source.

18. **(Previously Presented)** The method of claim 17, further comprising receiving light from the lamp and heating light source at a photodetector following reflection from an object.

19. **(Previously Presented)** The method of claim 17, further comprising scanning a document with the lamp and heating light source and receiving light from the lamp and heating light source by way of the document.

20. **(Previously Presented)** The method of claim 17, wherein the lamp is a fluorescent lamp.

21. **(Previously Presented)** The method of claim 20, wherein the lamp is a cold cathode fluorescent lamp.

22. **(Currently Amended)** The method of claim 17, ~~wherein the~~ further comprising scanning a document.

23. **(Currently Amended)** A method for making an illuminating device comprising:

providing a lamp;

providing a heating light source having a warm-up time period considerably less than that of the lamp;

providing a timer; and

coupling a controller to the lamp, heating, light source, and timer, the controller configured to power the lamp and heating light source, to start a timer upon powering of the lamp and heating light source, and to turn off the heating light source upon expiration of a predetermined time period.

24. **(Previously Presented)** The method of claim 23, further comprising positioning a photodetector in relation to the lamp and heating light source to receive light from the lamp and heating light source by way of a document.

25. **(Previously Presented)** The method of claim 24, wherein the lamp is a fluorescent lamp.

26. **(Previously Presented)** The method of claim 24, wherein the lamp is a cold cathode fluorescent lamp.

27. **(Previously Presented)** A device comprising:
a first means for illuminating;
a second means for illuminating having a warm-up period less than that of the first means for illuminating and generating more heat than the first means for illuminating; and
a means for powering the first and second means for illuminating for a time period and then turning off the second means for illuminating following expiration of the time period.

28. **(Previously Presented)** The device of claim 27, further comprising a means for detecting positioned to detect light from the first and second means for illuminating.

29. **(Previously Presented)** The device of claim 27, wherein the first means for illuminating is a cold cathode fluorescent lamp.

30. **(Previously Presented)** The device of claim 27, wherein the device is at least one of a flat bed scanner, a paper fed scanner, a copier, a Fax machine, and a multi-function product (MFP).